



Protective Gloves Rottex

Size:	M / 8	L / 9	XL / 10	XXL / 11
Ref:	11 605	11 606	11 607	11 608

Packing: 12 pairs per polybag
120 pairs per carton

Standards applied:
EN420:2003+A1, EN 388:2003, Regulation (EU) 2016/425



EEC Product Safety and Quality Test

Protection against mechanical risks EN 388



Test criteria

Abrasion resistance (Cycles)
Blade cut resistance – Coupe-Test (Index)
Tear resistance (Newton)
Puncture resistance (Newton)

0 = lowest performance level; 5 = highest performance level

Performance level

0	1	2	3	4	(0-4)	
0	1	2	3	4	5	(0-5)
0	1	2	3	4	(0-4)	
0	1	2	3	4	(0-4)	

CE 0120

EU Type-Examination by: SATRA Technology Centre Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

User and Care Instructions

EN User Instructions for Protective Gloves of PPE Category II according to Regulation (EU) 2016/425:

Checking: Prior to use check the gloves for holes, cracks, defects and change of glove material. Replace defective gloves. Hand protection and a secure grip can only be provided by gloves which fit the user adequately. If gloves have been tested physically the test results only refer to coated/reinforced areas for new and unused gloves.

Storage: Store gloves at room temperature in a dry and well ventilated place without folding them. Avoid penetration of sunlight and heat radiation. Storage condition and storage time can lower performance levels. Manufacturer assumes no responsibility for changed glove properties due to storage, washing and chemical treatments.

Transport: Only transport gloves in their original packing.

Use: Before using gloves wash and dry hands carefully. One pair of working gloves should not be worn continuously for more than two hours. If gloves are worn continuously for long periods, it is recommended to change between several pairs. Observe performance levels of the gloves. Do not use the glove in vicinity of any rotating component where there is a risk of glove being trapped and pulled into the machine. Not suitable for use with electrical components. Wash hands thoroughly after wearing gloves and apply a suitable hand creme. Gloves should be dry before wearing them again. Specified protection levels are only provided on coated/reinforced areas. After contamination deterioration of glove material performance is possible. Employer and user must decide whether the gloves protect against the hazards which may occur at the respective work situation.

Durability: The durability depends on the degree of deterioration and the intensity of use in the respective area of application, but a maximum of two years. A precise information of time is therefore not possible.

Cleaning: After use, depending on how dirty the gloves are, shake off the dust and dirt or brush with a soft brush. Do not rub. Dry in well ventilated area. Specified protection levels apply only for new gloves. Washing can reduce the performance level.

Disposal: Correct handling requires the gloves to be disposed of in the household waste. Contaminated protective gloves which may pose a risk are to be disposed of professionally. Information can be obtained from the relevant waste disposal authorities.

Caution: Producer is not aware of any substances that can cause allergies when using the glove. This product is not a chemical protection glove. You can obtain the declaration of conformity through: www.sanger.de

Sänger GmbH • Industriegebiet Herdwiesen • Zeller Weg 30 • 74575 Schrozberg / Germany • www.sanger.de

Copyright © 05/19 Sänger GmbH